

## ACCTLCERT + ACCTLHTCERT:

| Typ       | measurement range | standard point 1 [°C] | standard point 2 [°C] | standard point 3 [°C] |
|-----------|-------------------|-----------------------|-----------------------|-----------------------|
| 05M       | 990 - 2000°C      | 1000                  | 1200                  | 1400                  |
| 1ML       | 485 - 1050°C      | 500                   | 780                   | 1000                  |
| 1MH       | 650 - 1800°C      | 660                   | 1000                  | 1400                  |
| 1MH1      | 800 - 2200°C      | 820                   | 1000                  | 1400                  |
| 2ML       | 250 - 800°C       | 275                   | 500                   | 780                   |
| 2MH       | 385 - 1600°C      | 395                   | 820                   | 1400                  |
| 2MH1      | 490 - 2000°C      | 500                   | 820                   | 1400                  |
| 3ML       | 50-400°C          | 110                   | 166                   | 340                   |
| 3MH       | 100-600°C         | 110                   | 225                   | 500                   |
| 3MH1      | 150 - 1000°C      | 166                   | 500                   | 970                   |
| 3MH2      | 200 - 1500°C      | 225                   | 500                   | 1400                  |
| 3MH3      | 250 - 1800°C      | 275                   | 500                   | 1400                  |
| 3MH4      | 350 - 2500°C      | 395                   | 820                   | 1400                  |
| CTLLT     | -50 - 975°C       | Ambient               | 166                   | 500                   |
| CTLLT DCI | -50 - 975°C       | Ambient               | 166                   | 350                   |
| CTLLTF    | -50 - 975°C       | Ambient               | 166                   | 500                   |
| P7        | 0 - 710°C         | 50                    | 166                   | 500                   |
| G5L/G7    | 100 - 1200°C      | 110                   | 500                   | 1000                  |
| G5H       | 250 - 1650°C      | 275                   | 500                   | 1000                  |
| F2        | 200 - 1450°C      | 500                   | 1000                  | 1400                  |
| MT/F6/G5F |                   | 225                   | 500                   | 1000                  |

## ACCSLCERT + ACCSLHTCERT:

| Typ      | measurement range | standard point 1 [°C] | standard point 2 [°C] | standard point 3 [°C] |
|----------|-------------------|-----------------------|-----------------------|-----------------------|
| CSL2M(L) | 250 - 800         | 275                   | 500                   | 780                   |
| CSL2M(H) | 385 - 1600°C      | 395                   | 820                   | 1400                  |
| CSLLT    | -40 - 975°C       | Ambient               | 166                   | 500                   |
| CSLHS    | -20 - 150°C       | Ambient               | 70                    | 110                   |
| CSLG5HF  | 200 - 1450°C      | 210                   | 500                   | 1000                  |

## ACCTCERT + ACCTHCERT:

| Typ               | measurement range | standard point 1 [°C] | standard point 2 [°C] | standard point 3 [°C] |
|-------------------|-------------------|-----------------------|-----------------------|-----------------------|
| 1ML               | 485 - 1050°C      | 500                   | 800                   | 1000                  |
| 1MH               | 650 - 1800°C      | 660                   | 1000                  | 1400                  |
| 1MH1              | 800 - 2200°C      | 820                   | 1000                  | 1400                  |
| 2ML               | 250 - 800°C       | 275                   | 500                   | 780                   |
| 2MH               | 385 - 1600°C      | 395                   | 500                   | 1000                  |
| 2MH1              | 490 - 2000°C      | 500                   | 1000                  | 1400                  |
| 3ML               | 50 - 400°C        | 70                    | 200                   | 340                   |
| 3MH               | 100 - 600°C       | 110                   | 340                   | 500                   |
| 3MH1              | 150 - 1000°C      | 175                   | 500                   | 980                   |
| 3MH2              | 200 - 1500°C      | 225                   | 500                   | 1000                  |
| 3MH3              | 250 - 1800°C      | 275                   | 500                   | 1400                  |
| P3                | 50 - 400°C        | 108,3                 | 225                   | 340                   |
| P7                | 0 - 710°C         | Ambient               | 110                   | 510                   |
| G5L               | 100 - 1200°C      | 108,3                 | 500                   | 1000                  |
| G5H               | 250 - 1650°C      | 275                   | 500                   | 1000                  |
| CT LT02/15/22     | -50 - 975         | Ambient               | 110                   | 510                   |
| CT Fast LT15F/25F | -50 - 975         | Ambient               | 110                   | 510                   |
| CT Hot LT02H/10H  | -40 - 975         | Ambient               | 110                   | 510                   |
| CT Ratio (old)    | 700 - 1800        | 710                   | 1000                  | 1400                  |

## ACCSCERT + ACCSHTCERT:

| Typ    | measurement range | standard point 1 [°C] | standard point 2 [°C] | standard point 3 [°C] |
|--------|-------------------|-----------------------|-----------------------|-----------------------|
| LT/H   | -40 - 1030°C      | Ambient               | 108.3                 | 500                   |
| HS     | -20 - 150°C       | Ambient               | 70                    | 108.3                 |
| 2MH    | 385 - 1600°C      | 395                   | 500                   | 1000                  |
| 2ML    | 250 - 800°C       | 260                   | 500                   | 780                   |
| 3MH    | 100 - 600°C       | 108,3                 | 260                   | 500                   |
| 3ML    | 50 - 350°C        | 70                    | 200                   | 340                   |
| 2ML v3 | 250 - 800°C       | 265                   | 340                   | 500                   |
| 2MH v3 | 385 - 1600°C      | 395                   | 800                   | 1400                  |
| 3ML v3 | 50 - 350°C        | 55                    | 108,3                 | 340                   |
| 3MH v3 | 100 - 600°C       | 108,3                 | 200                   | 500                   |